

Target Solar Company WalSolar Industrial Corporation

150W DC Solar Street Lights

A、Light

1. Cover Material: Aluminum Alloy
2. Light: Ceramic Metal Halide Lamp 70W*1
3. Transparent Cover: Tempered glass, High temperature resistance, Anti-rain
4. Protection Degree: IP65
5. Luminous Flux: 3200 lm

B、Light Pole

1. Shaft using $\phi = 4$ "x4.2t over galvanized steel pole
2. Base plate made of f 20T steel plate
3. Solar panel mounting rack made of angle steel 50x50-4t
4. Control box made using SS41P-1.5t galvanized steel

C、Foundation Screw

1. $\Psi 25 \times 1000$ Foundation Screw

D、Power Control


1. Power Collection System: Solar Module 150W x1pc, $V_{mp}=34.4V$, $I_{mp}=4.36A$, Dimension 1580 x 808 x 80mm
2. Power Storage : Silicon Power Battery 12V, 80AH*2pcs
3. Charge Controller :
 - Automatic turn on when sunset
 - Self setting light on time
 - Battery over charging and discharging protection
4. Light on time: Automatically daily switch on light when sunset, for 6 hours

E、Size

1. Total pole height - 6M
2. Lamp mounting height 5M

F、Others

1. The surface of the poles have been dealing with hot-dip galvanizing, the appearance is dealt with powder coating technology, and color should be ordered separately.
2. Solar panels should be mounted facing south for the direction of the sun and should avoid shading.
3. The product warranty: 1 year.



※This document is the exclusive property of WSIC and shall not be reproduced or copied or transformed to any other format without prior permission of WSIC.

2F, No.7-1, Ln. 3, Xinhe 1st Rd., Tainan City 702, Taiwan

TEL: +886-6-2648199 FAX: +886-6-2657069

www.walsolar.biz

info@wal-solar.com